

# SASSO 60 square downlight

semi-recessed

048-30011171S 002-90746



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed  
white , RAL9016/black <sup>1</sup>  
Inner colour black  
front IP40 , back IP20  
503 lm

## LED

4000 K  
CRI ≥ 90  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 98 , R<sub>f</sub>: 90 , R<sub>[1-15]</sub>: 88  
MR 0.8  
MDER 0.72

## Optical

spot  
beam angle 12°  
UGR < 13  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2  
system 10.4 W  
inset 8.8 W  
36 Vf  
250 mA  
PC2 220-240V  
system 48 lm/W<sup>3</sup>  
inset 57 lm/W<sup>4</sup>  
1 DALI Addr.

## Physical


length 72 mm  
width 72 mm  
height 75 mm  
0.52 kg

## Cutout


diameter 60 mm  
recessed depth 120 mm

Square semi-recessed spotlight made of aluminium; surface white (housing/light inset); luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 13; degree of protection IP40; PC2 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>4</sup> incl. optical losses

## Installation instructions



## Lighting calculator

