

SASSO 60 square downlight

trim 2 lamps

048-2612017W 048-2699317 002-90746



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

white , RAL9016 ¹

Mounting set traffic white

front IP44 , back IP20

1860 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 90 , R_{t(1-15)}: 87

MR 0.6

MDER 0.54

Optical

wide flood

beam angle 52°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

220-240 V

system 20.5 W

inset 8.7 W

36 V

250 mA

total insets 17.4 W

PC2

system 91 lm/W³

inset 107 lm/W³

1 DALI Addr.

Physical

trim

length 147 mm

width 81 mm

height 48 mm

0.34 kg

Cutout

length 138 mm

width 73 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 100 mm

¹ RAL code ² Value of containing product at full load (undimmed)

³ incl. optical losses and the efficiency of the operating device (converter)

Light distribution





Product drawing



90
non DIM

100
DALI-2

73 x 138



SASSO 60 square downlight

trim 2 lamps

048-2612017W 048-2699317 002-90746



Project / Type

Notes

Count / Date

Installation
instructions



Lighting
calculator

