

# SASSO 60 round downlight

trim

048-2602014F 048-2696317 002-90746



Project / Type	
Notes	
Count / Date	



--	--	--	--	--

### General

Ceiling , Recessed
rotation 360°
matt silver
Mounting set traffic white
front IP44 , back IP20
921 lm

### LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 87
MR 0.6
MDER 0.54

### Optical

flood
beam angle 42°
UGR < 16 , ≥65° <1500 cd/m <sup>2</sup>
P <sub>stLM</sub> ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 42° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m<sup>2</sup>; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Electrical

DALI-2
system 10.2 W
inset 8.7 W
36 Vf
250 mA
PC2 220-240V
system 90 lm/W <sup>2</sup>
inset 106 lm/W <sup>3</sup>
1 DALI Addr.


### Physical

trim
diameter 80 mm
height 48 mm
0.27 kg

### Cutout

diameter 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

### Light distribution



### Product drawing



# SASSO 60 round downlight

trim

048-2602014F 048-2696317 002-90746



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

