

# SASSO 60 square downlight


semi-recessed

048-30012117S 002-90742




Square semi-recessed spotlight made of aluminium; surface black powder coated; Inner colour lacquered in white; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR  $\leq 19$ ; degree of protection IP40; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



## General

|                               |
|-------------------------------|
| Ceiling , Semi-Recessed       |
| black , RAL 9005 <sup>1</sup> |
| Inner colour white            |
| front IP40 , back IP20        |
| 933 lm                        |
| fixture 86 lm/W <sup>2</sup>  |

## LED

|   |
|---|
| 3500 K  |
| CRI $\geq 90$   |
| initial MacAdam $\leq 2$ SDCM   |
| R <sub>g</sub> : 99 , R <sub>r</sub> : 90 , R <sub>t(1-15)</sub> : 87 |
| MR 0.6  |
| MDER 0.54   |

## Optical

|                               |
|-------------------------------|
| spot                          |
| beam angle 15°                |
| UGR $< 19$                    |
| PstLM $\leq 1.0$ <sup>3</sup> |
| SVM $\leq 0.4$ <sup>3</sup>   |

## Electrical

|                |
|----------------|
| non DIM        |
| 220-240 V      |
| system 12.8 W  |
| fixture 10.9 W |
| 36 Vf          |
| 300 mA         |
| PC2            |

## Physical

|              |
|--------------|
| length 72 mm |
| width 72 mm  |
| height 75 mm |
| 0.46 kg      |

## Cutout

|                      |
|----------------------|
| diameter 60 mm       |
| recessed depth 85 mm |

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator



SASSO 60 square  
downlight

semi-recessed

048-30012117S 002-90742



Project / Type

Notes

Count / Date

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 43                 |
| B13                            | 55                 |
| B16                            | 68                 |
| B20                            | 85                 |
| C10                            | 72                 |
| C13                            | 94                 |
| C16                            | 116                |
| C20                            | 145                |

Components

POWER SUPPLY

|      |            |                   |
|------|------------|-------------------|
| TYPE | L·W·H (MM) | ARTICLE NUMBER(S) |
| 10 W | 65-39-20   | 002-90742         |



Optional electrical accessories

DIN RAIL POWER SUPPLY

|       |            |                   |
|-------|------------|-------------------|
| TYPE  | L·W·H (MM) | ARTICLE NUMBER(S) |
| 160 W | 72-90-63   | 005-6520210       |



DIN RAIL LED DRIVER

|                                |            |                   |
|--------------------------------|------------|-------------------|
| TYPE                           | L·W·H (MM) | ARTICLE NUMBER(S) |
| DALI-2   200-1050 mA   2 x 42W | 36-88-59   | 005-6121030       |

