

JUST 55

MOVE IT 25 / 25 S / 45
050-0143937S



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface white powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 14° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;

UGR

≤ 10

CRI

≥ 90

1ADDR

General

Ceiling , Track

tilt max 90°

rotation 360°

white , RAL9016 ¹

IP20

1280 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 91 , R_{1-15}: 87

MR 0.52

MDER 0.47

Optical

spot

beam angle 14°

Electrical

DALI-2 single control

12.7 W

PC3 48V

101 lm/W

1 DALI Addr.


Physical

diameter 55 mm

height 100 mm

0.3 kg


Light distribution



spot 14°

h (m)	E0° (lx)	ø (m)
1	10600	0.25
2	2700	0.51
3	1200	0.76
4	700	1.01
5	400	1.27

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

