

# JUST 32 FOCUS

MOVE IT 25

050-0111018



Project / Type

Notes

Count / Date



## General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

black , RAL 9005 <sup>1</sup>

IP20

332<sup>2</sup>-411<sup>3</sup> lm

optical inset 80<sup>2</sup>-99<sup>3</sup> lm/W<sup>4</sup>

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 90 , R<sub>t(1-5)</sub>: 87

MR 0.6

MDER 0.54

## Optical

focus

beam angle 17°<sup>2</sup>-43°<sup>3</sup>

PstLM ≤ 1.0<sup>2</sup> 3 5

SVM ≤ 0.4<sup>2</sup> 3 5

## Electrical

non DIM

48 V

fixture 5.5 W

fixture 60<sup>2</sup>-75<sup>3</sup> lm/W<sup>6</sup>

optical inset 4.2 W

PC3

## Physical

diameter 32 mm

height 73 mm

0.2 kg


<sup>1</sup> RAL code <sup>2</sup> beam angle min <sup>3</sup> beam angle max

<sup>4</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>5</sup> Value of containing product at full load (undimmed)


<sup>6</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



focus 43°


h (m)	E0° (lx)	ø (m)
1	740	0.80
2	185	1.59
3	82	2.39
4	46	3.18
5	30	3.98



focus 17°

h (m)	E0° (lx)	ø (m)
1	2570	0.30
2	640	0.59
3	290	0.89
4	160	1.19
5	100	1.49

## Product drawing



## Installation instructions

