

# JUST 55

MOVE IT 25 / 25 S / 45

050-0143138M



Project / Type

Notes

Count / Date



## General

Ceiling , Track

tilt max 90°

rotation 360°

black , RAL 9005 <sup>1</sup>

IP20

1310 lm

optical inset 121 lm/W<sup>2</sup>

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 98 , R<sub>r</sub>: 90 , R<sub>t(1-15)</sub>: 88

MR 0.8

MDER 0.72

## Optical

medium

beam angle 23°

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2 single control

48 V

fixture 12.7 W

fixture 103 lm/W<sup>4</sup>

optical inset 10.8 W

PC3

1 DALI Addr.

## Physical

diameter 55 mm

height 100 mm

0.3 kg


<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses

<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


## Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	6030	0.41
2	1510	0.82
3	670	1.22
4	380	1.63
5	240	2.04

## Product drawing



## Installation instructions



## Lighting calculator

