

JUST 55

MOVE IT 25 / 25 S / 45
050-014303XS



Project / Type

Notes

Count / Date



General

Ceiling , Track

tilt max 90°

rotation 360°

special colours

IP20

1330 lm

optical inset 123 lm/W¹

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 90 , R_{t1-15}: 87

MR 0.6

MDER 0.54

Optical

spot

beam angle 14°

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2 single control

48 V

fixture 12.7 W

fixture 105 lm/W³

optical inset 10.8 W

PC3

1 DALI Addr.

Physical

diameter 55 mm

height 100 mm


0.3 kg

¹ OPTICAL INSET: incl. consideration of optical losses

² Value of containing product at full load (undimmed)

³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


Light distribution



spot 14°

h (m)	E0° (lx)	ø (m)
1	11000	0.25
2	2800	0.51
3	1200	0.76
4	700	1.01
5	400	1.27

Product drawing



Installation instructions



Lighting calculator

