

JUST 45 MOVE IT 25 / 25 S / 45

050-013113XM



Project / Type _____


Notes _____

Count / Date _____



Cylindrical spotlight in aluminium; surface special colours powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 23° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;

Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	4770	0.40
2	1190	0.81
3	530	1.21
4	300	1.62
5	190	2.02

Product drawing



General

Ceiling , Track _____

tilt max 90° _____

rotation 360° _____

special colours _____

IP20 _____

947 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 98 , R_f: 90 , R_{t(1-15)}: 88 _____

MR 0.8 _____

MDER 0.72 _____

Optical

medium _____

beam angle 23° _____

Electrical

DALI-2 single control _____

10.9 W _____

PC3 48V _____

87 lm/W _____

1 DALI Addr. _____

Physical

diameter 45 mm _____

height 68 mm _____

0.2 kg _____

Installation instructions



Lighting calculator

