

JUST 45 MOVE IT 25 / 25 S / 45

050-0131138V



Project / Type

Notes

Count / Date



General

Ceiling , Track

tilt max 90°

rotation 360°

black , RAL 9005 ¹

IP20

323 lm

optical inset 71 lm/W²

LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 94 , R_r: 87 , R₍₁₋₁₅₎: 90

MR 0.86

MDER 0.78

Optical

super spot

beam angle 8°

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2 single control

48 V

fixture 6.0 W

fixture 54 lm/W⁴

optical inset 4.5 W

PC3

1 DALI Addr.

Physical

diameter 45 mm

height 68 mm

0.2 kg


¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)

⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


Light distribution



super spot 8°

h (m)	E0° (lx)	ø (m)
1	11300	0.14
2	2800	0.28
3	1300	0.41
4	700	0.55
5	500	0.69

Product drawing



Installation instructions



Lighting calculator

