

# JUST 45 MOVE IT 25 / 25 S / 45

050-0131137F



Project / Type


Notes

Count / Date



Cylindrical spotlight in aluminium; surface white powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;


## Light distribution



flood 44°

h (m)	EO° (lx)	ø (m)
1	1850	0.82
2	460	1.64
3	210	2.45
4	120	3.27
5	70	4.09

## Product drawing



## General

Ceiling , Track

tilt max 90°

rotation 360°

white , RAL9016 <sup>1</sup>

IP20

1000 lm

## LED

4000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 98 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 88

MR 0.8

MDER 0.72

## Optical

flood

beam angle 44°

## Electrical

DALI-2 single control

10.9 W

PC3 48V

92 lm/W

1 DALI Addr.

## Physical

diameter 45 mm

height 68 mm

0.2 kg

<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

