

JUST 45 MOVE IT 25 / 25 S / 45

050-0131118F



Project / Type

Notes

Count / Date



General

Ceiling , Track

tilt max 90°

rotation 360°

black , RAL 9005 ¹

IP20

1000 lm

optical inset 122 lm/W²

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98 , R_r: 90 , R_{t(1-5)}: 88

MR 0.8

MDER 0.72

Optical

flood

beam angle 44°

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

non DIM

48 V

fixture 10.9 W

fixture 92 lm/W⁴

optical inset 8.2 W

PC3

Physical

diameter 45 mm

height 68 mm

0.2 kg


¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)

⁴ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


Light distribution



flood 44°

h (m)	E0° (lx)	ø (m)
1	1850	0.82
2	460	1.64
3	210	2.45
4	120	3.27
5	70	4.09

Product drawing



Installation instructions



Lighting calculator

