

# MOVE IT 10 track square curve direct

suspended  
030-153203P



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

white , RAL9016/RAL9005 <sup>1</sup>

black

IP20

Electrical

DALI-2

PC3 48V

Physical

width 19 mm

height 24 mm

centerline radius 500 mm

segment 90°

<sup>1</sup> RAL code

Installation  
instructions



Thin extruded aluminium profile with 24 mm height and 10 mm width groove; CURVE channel 90°; for suspended mounting (1500 mm cable suspension as an accessory); height adjustment without tools; with integrated power track profile for take off of supply voltage and DALI-2 signal; surface white; powder coated / anodised; light insets can be installed and moved without tools by means of clip mount; degree of protection IP20; PC3 48V; accessories are listed separately;

Product drawing



[‘030-153203P’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)