

# TRACK 60 CONEX plug / socket

surface / suspended system  
058-4824037



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL 9010 <sup>1</sup>

IP20

Electrical

DALI-2

220-240 V

PC1

Physical

length 1181 mm

width 60 mm

height 60 mm


<sup>1</sup> RAL code

Installation instructions



Cylindrical power track module in aluminium; for CONEX lighting system; surface white powder coated; for wall-/ceiling surface mounting or suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); easy installation using ceiling clips (available as an accessory) or with integrated toolless suspension height adjustment; freely positioned attachment to the power track; with integrated 1-phase power track (L, N, PE) + 2 DALI copper conductors; electrical connection of the power tracks via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; power track connection rotatable around its own axis, which means that any spatial angle can be realized; insets, incl. high power adapter + converter can be installed flexibly and without tools; degree of protection IP20; PC1; 220-240 V; accessories are listed separately;

Product drawing



[058-4824037] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)