

SASSO 100 square wallwasher/floor

trim 2 lamps

048-2750219W 048-279931G 002-90766




Project / Type	
Notes	
Count / Date	



Recessed square spotlight in die-cast aluminium; 2 lamps; surface gold; installation without tools in mounting set due to patented ball catch system; rectangular installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed	
gold , RAL 260-M ¹	
Mounting set white aluminium	
IP20	
4020 lm	
fixture 138 lm/W ²	

LED

3500 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 2 SDCM	
R _g : 99 , R _f : 90 , R ₍₁₋₁₅₎ : 89	
MR 0.7	
MDER 0.64	

Optical

wallwasher floor	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical

non DIM	
220-240 V	
system 34 W	
fixture 14.6 W	
36 Vf	
450 mA	
fixture 29.2 W	
PC2	

Physical

trim	
length 218 mm	
width 118 mm	
height 96 mm	
0.6 kg	

Cutout

length 210 mm	
width 112 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 100 mm	

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

