

SASSO 100 round wallwasher trimless soft acoustic ceiling

048-2740914A 048-2796198 002-90780



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____

rotation 360° _____

matt silver _____

Mounting set traffic black for acoustic ceilings _____

IP20 _____

2270 lm _____

fixture 96 lm/W¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 101 , R_r: 90 , R_{t(1-5)}: 88 _____

MR 0.51 _____

MDER 0.46 _____

Optical

wallwasher _____

Electrical

non DIM _____

220-240 V _____

system 27.8 W _____

fixture 23.7 W _____

36 Vf _____

650 mA _____

PC2 _____

Physical

trimless for acoustic ceiling _____

diameter 114 mm _____

height 96 mm _____

0.68 kg _____

Cutout

diameter 100 mm _____


min. ceiling thickness 25 mm _____

max. ceiling thickness 40 mm _____

recessed depth 120 mm _____

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses
SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Light distribution



Product drawing



Installation instructions



Lighting calculator

