

# SASSO 100 round wallwasher/floor trim soft acoustic ceiling

048-2740911W 048-2796398 002-90780



Project / Type	
Notes	
Count / Date	



<b>General</b>
Ceiling , Recessed
rotation 360°
black , RAL 9005 <sup>1</sup>
Mounting set traffic black for acoustic ceilings
IP20
2530 lm
fixture 118 lm/W <sup>2</sup>

<b>LED</b>
2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 87
MR 0.52
MDER 0.47


<b>Optical</b>
wallwasher floor

<b>Electrical</b>
non DIM
220-240 V
system 25.2 W
fixture 21.5 W
36 Vf
650 mA
PC2

<b>Physical</b>
with trim for acoustic ceiling
diameter 114 mm
height 96 mm
0.65 kg

<b>Cutout</b>
diameter 100 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 100 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses

## Installation instructions



## Lighting calculator

