

# SASSO 100 round wallwasher/floor trim soft acoustic ceiling

048-2740114W 048-2796397 002-90780



Project / Type

Notes

Count / Date



General
Ceiling , Recessed
rotation 360°
matt silver
Mounting set signal white for acoustic ceilings
IP20
2810 lm
fixture 131 lm/W <sup>1</sup>

LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 98 , R <sub>r</sub> : 90 , R <sub>t1-15</sub> : 88
MR 0.8
MDER 0.72

Optical
wallwasher floor


Electrical
non DIM
220-240 V
system 25.2 W
fixture 21.5 W
36 Vf
650 mA
PC2

Physical
with trim for acoustic ceiling
diameter 114 mm
height 96 mm
0.65 kg


Cutout
diameter 100 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 100 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



[048-2740114W 048-2796397 002-90780] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)