


048-2730911F 048-2797318 002-90766



Ceiling , Recessed  
tilt max 30°  
black , RAL 9005 <sup>1</sup>  
Mounting set jet black  
front IP40 , back IP20  
1550 lm  
fixture 102 lm/W<sup>2</sup>

2700 K  
CRI  $\geq 90$   
L80 / 50000 h  
initial MacAdam  $\leq 2$  SDCM  
R<sub>g</sub>: 97, R<sub>f</sub>: 91, R<sub>{f-15}</sub>: 87  
MR 0.52  
MDER 0.47

flood
beam angle 45°
UGR ≤ 16, ≥65° <1500 cd/m²
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>

non DIM
220-240 V
system 17.9 W
fixture 15.2 W
36 Vf
450 mA
PC2

trim	
length 118 mm	
width 118 mm	
height 95 mm	
0.51 kg	

length 112 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses  
 SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

Technical drawings of the DALI-I-2 and DALI-II-2 lighting fixtures. The DALI-I-2 drawing includes a top view showing a 100mm square, a 112x112mm square, and a 118mm square, and a side view showing a 30-degree angle and a 50mm height. The DALI-II-2 drawing includes a top view showing a 112x112mm square and a 118mm square, and a side view showing a 112x112mm square and a 118mm height.

# SASSO 100 square adjustable

trim  
048-2730911F 048-2797318 002-90766



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

