

# SASSO 100 round adjustable

trim

048-2720917X 048-2796318 002-90766




|                |
|----------------|
| Project / Type |
| Notes          |
| Count / Date   |



Round recessed spotlight in die-cast aluminium; 1 lamp; surface white; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 63° beam; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

|                               |
|-------------------------------|
| Ceiling , Recessed            |
| tilt max 30°                  |
| rotation 360°                 |
| white , RAL 9016 <sup>1</sup> |
| Mounting set jet black        |
| front IP40 , back IP20        |
| 1500 lm                       |
| fixture 98 lm/W <sup>2</sup>  |

## LED

|  |
|--|
| 2700 K   |
| CRI $\geq 90$  |
| L80 / 50000 h  |
| initial MacAdam $\leq 2$ SDCM  |
| R <sub>g</sub> : 97 , R <sub>f</sub> : 91 , R <sub>{1-15}</sub> : 87 |
| MR 0.52  |
| MDER 0.47  |

## Optical

|                               |
|-------------------------------|
| super wide flood              |
| beam angle 63°                |
| PstLM $\leq 1.0$ <sup>3</sup> |
| SVM $\leq 0.4$ <sup>3</sup>   |

## Electrical

|                |
|----------------|
| non DIM        |
| 220-240 V      |
| system 17.9 W  |
| fixture 15.2 W |
| 36 Vf          |
| 450 mA         |
| PC2            |

## Physical

|                 |
|-----------------|
| trim            |
| diameter 118 mm |
| height 95 mm    |
| 0.46 kg         |

## Cutout

|                              |
|------------------------------|
| diameter 108 mm              |
| min. ceiling thickness 2 mm  |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm        |

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)

# SASSO 100 round adjustable

trim

048-2720917X 048-2796318 002-90766



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

