

SASSO 100 round adjustable

trim 2 lamps

048-2720919F 048-2798317 002-90780



Project / Type _____


Notes _____

Count / Date _____



Round recessed spotlight in die-cast aluminium; 2 lamps; surface gold; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 45° beam; UGR ≤ 16 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed _____

tilt max 30° _____

rotation 360° _____

gold , RAL 260-M¹ _____

Mounting set traffic white _____

front IP40 , back IP20 _____

4260 lm _____

fixture 94 lm/W² _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 97 , R_f: 91 , R_{1-15}: 87 _____

MR 0.52 _____

MDER 0.47 _____

Optical

flood _____

beam angle 45° _____

UGR ≤ 16 , $\geq 65^\circ < 3000$ cd/m² _____

Electrical

non DIM _____

220-240 V _____

system 52 W _____

fixture 22.7 W _____

36 Vf _____

650 mA _____

fixture 45 W _____

PC2 _____

Physical

trim _____

length 218 mm _____

width 118 mm _____

height 95 mm _____

0.56 kg _____

Cutout

diameter 105 mm _____

length 205 mm _____

width 105 mm _____

min. ceiling thickness 2 mm _____

max. ceiling thickness 25 mm _____

recessed depth 100 mm _____

¹ RAL code
² incl. consideration of optical losses & internal control unit losses



SASSO 100 round adjustable

trim 2 lamps

048-2720919F 048-2798317 002-90780



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

