

SASSO 100 round adjustable

trim

048-2720019S 048-2796317 002-90780



Project / Type

Notes

Count / Date



| |
|------------------------------|
| General |
| Ceiling , Recessed |
| tilt max 30° |
| rotation 360° |
| gold , RAL260-M ¹ |
| traffic white |
| front IP40 , back IP20 |
| 1990 lm |

| |
|--|
| LED |
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _r : 90 , R _{t(1-5)} : 87 |
| MR 0.6 |
| MDER 0.54 |

| |
|----------------|
| Optical |
| spot |
| beam angle 18° |
| UGR < 13 |


| |
|-------------------|
| Electrical |
| non DIM |
| 26.7 W |
| inset 22.7 W |
| 36 V _f |
| 650 mA |
| PC2 220-240V |
| 75 lm/W |
| inset 88 lm/W |

| |
|-----------------|
| Physical |
| trim |
| diameter 118 mm |
| height 95 mm |
| 0.45 kg |

| |
|------------------------------|
| Cutout |
| diameter 108 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm |

¹ RAL code

Light distribution



Product drawing



Installation instructions



Lighting calculator

