

SASSO 100 round downlight

trim

048-2700014W 048-2796317 002-90780



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



| | | | |
|--|--|--|--|
| | | | |
|--|--|--|--|

General

| |
|-------------------------------|
| Ceiling , Recessed |
| matt silver |
| Mounting set traffic white |
| front IP44 , back IP20 |
| 2380 lm |
| fixture 105 lm/W ¹ |

LED

| |
|----------------------------------------------------------------------|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _f : 90 , R ₍₁₋₁₅₎ : 87 |
| MR 0.6 |
| MDER 0.54 |

Optical

| |
|------------------|
| wide flood |
| beam angle 65° |
| ≥65° <1500 cd/m² |

Electrical

| |
|----------------|
| non DIM |
| 220-240 V |
| system 26.7 W |
| fixture 22.7 W |
| 36 Vf |
| 650 mA |
| PC2 |

Physical


| |
|-----------------|
| trim |
| diameter 118 mm |
| height 75 mm |
| 0.45 kg |

Cutout

| |
|------------------------------|
| diameter 108 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 80 mm |

¹ incl. consideration of optical losses & internal control unit losses

Light distribution



Product drawing



Installation instructions



Lighting calculator

