

SASSO 60 emergency light

pro trimless soft acoustic ceiling

048-2693231 048-2696198



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____

rotation 360° _____

black , RAL 9005 ¹ _____

Mounting set traffic black for acoustic ceilings _____

IP20 _____

206², 208³, 217⁴ lm _____

LED

6500 K _____

CRI ≥ 80 _____

Optical

emergency light _____

beam angle 21°², 103°x25°³, 149°x150°⁴ _____

Electrical

220-240 V _____

system 1.0 W _____

system 206², 208³, 217⁴ lm/W⁵ _____

PC2 _____

Physical

trimless for acoustic ceiling _____

diameter 80 mm _____

height 94 mm _____


0.32 kg _____

Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; Pro DALI with monitoring via DALI; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2; light source not replaceable;

Light distribution



Product drawing



Cutout

diameter 74 mm _____

min. ceiling thickness 25 mm _____

max. ceiling thickness 40 mm _____

recessed depth 110 mm _____

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens
⁵ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

