

SASSO 60 emergency light
selftest trim soft acoustic
ceiling

048-2693221 048-2696398



Project / Type _____

Notes _____

Count / Date _____




Round LED emergency light inset; surface lacquered in black; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim Traffic black; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; selftest with status LED; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2 220-240V; light source not replaceable;

Light distribution



Product drawing



General

Ceiling , Recessed _____

rotation 360° _____

black , RAL9005 ¹ _____

Traffic black _____

IP20 _____

206², 208³, 217⁴ lm _____

LED

6500 K _____

CRI ≥ 80 _____

Optical

emergency light _____

beam angle 21°², 103°x25°³, 149°x150°⁴ _____

Electrical

system 1.0 W _____

inset 1.0 W _____

200 mA _____

PC2 220-240V _____

system 206², 208³, 217⁴ lm/W⁵ _____

inset 206², 208³, 217⁴ lm/W⁶ _____

Physical

with trim for acoustic ceiling _____

diameter 80 mm _____

height 94 mm _____

0.34 kg _____

Cutout

diameter 74 mm _____

min. ceiling thickness 25 mm _____

max. ceiling thickness 40 mm _____

recessed depth 110 mm _____

¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens
⁵ incl. optical losses and the efficiency of the operating device (converter)
⁶ incl. optical losses

Installation instructions



Lighting calculator



SASSO 60 emergency light selftest trim soft acoustic ceiling

048-2693221 048-2696398



Project / Type

Notes

Count / Date

Components

MOUNTING SET trim for soft acoustic ceilings

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic black for acoustic ceilings	80	048-2696398



Electrical accessories

REPLACEMENT ACCUPACK

TYPE	ARTICLE NUMBER(S)
3h battery life	048-2693910

