

SASSO 60 round wallwasher/floor trim soft acoustic ceiling

048-2641414W 048-2696398 002-90762



Project / Type

Notes

Count / Date



General

Ceiling , Recessed

rotation 360°

matt silver

Traffic black

IP20

746 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 97 , R_f: 91 , R₍₁₋₁₅₎: 90

MR 0.53

MDER 0.48

Optical

wallwasher floor

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

9.7 W

inset 8.3 W

27 Vf

300 mA

PC2 220-240V

77 lm/W

inset 90 lm/W

1 DALI Addr.

Physical

with trim for acoustic ceiling

diameter 80 mm

height 48 mm

0.26 kg

Cutout

diameter 74 mm


min. ceiling thickness 25 mm

max. ceiling thickness 40 mm


recessed depth 110 mm

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim Traffic black; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

