


SASSO 60 round wallwasher/floor trimless soft acoustic ceiling

048-2641414W 048-2696198 002-90762




Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; Traffic black; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|--------------------|
| Ceiling , Recessed |
| rotation 360° |
| matt silver |
| Traffic black |
| IP20 |
| 746 lm |

LED

| |
|--|
| 2700 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 97 , R _f : 91 , R ₍₁₋₁₅₎ : 90 |
| MR 0.53 |
| MDER 0.48 |

Optical

| |
|-------------------------------|
| wallwasher floor |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Electrical

| |
|---------------|
| DALI-2 |
| 9.7 W |
| inset 8.3 W |
| 27 Vf |
| 300 mA |
| PC2 220-240V |
| 77 lm/W |
| inset 90 lm/W |
| 1 DALI Addr. |

Physical

| |
|-------------------------------|
| trimless for acoustic ceiling |
| diameter 80 mm |
| height 48 mm |
| 0.28 kg |

Cutout

| |
|------------------------------|
| diameter 74 mm |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 120 mm |

¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

