

SASSO 60 round downlight trimless soft acoustic ceiling


048-2602114S 048-2696198 002-90746



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 rotation 360°
 matt silver
 Traffic black
 front IP44 , back IP20
 614 lm

LED

4000 K
 CRI ≥ 90
 initial MacAdam ≤ 2 SDCM
 R_g: 98 , R_r: 90 , R_{t(1-15)}: 88
 MR 0.8
 MDER 0.72

Optical

spot
 beam angle 12°
 UGR < 16 , ≥65° <1500 cd/m²
 PstLM ≤ 1.0¹
 SVM ≤ 0.4¹

Electrical

DALI-2
 system 10.4 W
 inset 8.8 W
 36 Vf
 250 mA
 PC2 220-240V
 system 59 lm/W²
 inset 69 lm/W³
 1 DALI Addr.

Physical

trimless for acoustic ceiling
 diameter 80 mm
 height 48 mm
 0.28 kg

Cutout

diameter 74 mm
 min. ceiling thickness 25 mm
 max. ceiling thickness 40 mm
 recessed depth 120 mm


¹ Value of containing product at full load (undimmed)

² incl. optical losses and the efficiency of the operating device (converter)


³ incl. optical losses

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; installation without tools in mounting set due to patented ball catch system; round installation housing; Traffic black; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator



[048-2602114S 048-2696198 002-90746] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

21.11.2024