

SASSO 100 square adjustable

trim

048-2730019F 048-2797317 002-90789




| |
|----------------|
| Project / Type |
| Notes |
| Count / Date |




Recessed square spotlight in die-cast aluminium; 1 lamp; surface gold; 30° tiltable; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 44° beam; UGR ≤ 16 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|------------------------------|
| Ceiling , Recessed |
| tilt max 30° |
| gold , RAL260-M ¹ |
| Mounting set traffic white |
| front IP40 , back IP20 |
| 2230 lm |

LED

| |
|--|
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _f : 90 , R ₍₁₋₁₅₎ : 87 |
| MR 0.6 |
| MDER 0.54 |

Optical

| |
|---|
| flood |
| beam angle 44° |
| UGR < 16 , $\geq 65^\circ < 3000$ cd/m ² |
| P _{stLM} ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|---------------|
| DALI-2 |
| 26.7 W |
| inset 22.7 W |
| 36 Vf |
| 650 mA |
| PC2 220-240V |
| 84 lm/W |
| inset 98 lm/W |
| 1 DALI Addr. |

Physical

| |
|---------------|
| trim |
| length 118 mm |
| width 118 mm |
| height 95 mm |
| 0.53 kg |

Cutout

| |
|------------------------------|
| length 112 mm |
| width 112 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm |

¹ RAL code ² Value of containing product at full load (undimmed)



SASSO 100 square adjustable

trim

048-2730019F 048-2797317 002-90789



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

