

SASSO 100 square wallwasher

trim

048-2750217A 048-279731G 002-90767



Project / Type

Notes

Count / Date



General

Ceiling , Recessed
white , RAL 9016 ¹
Mounting set white aluminium
IP20
1760 lm
fixture 111 lm/W²

LED

3500 K
CRI \geq 90
L85 / 50000 h
initial MacAdam \leq 3 SDCM
R_g: 96 , R_f: 90 , R₍₁₋₁₅₎: 91
MR 0.74
MDER 0.67

Optical

wallwasher
PstLM \leq 1.0 ³
SVM \leq 0.4 ³

Electrical

DALI-2
220-240 V
system 18.6 W
fixture 15.8 W
36 Vf
450 mA
PC2

Physical

trim
length 118 mm
width 118 mm
height 96 mm
0.74 kg

Cutout

length 112 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 120 mm

¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)

Installation instructions




Lighting calculator



Recessed square spotlight in die-cast aluminium; 1 lamp; surface white; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3500 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

