

# SASSO 100 square wallwasher

trim

048-2750114A 048-279731G 002-90789



Project / Type

Notes

Count / Date



### General

Ceiling , Recessed

matt silver

Mounting set white aluminium

IP20

2520 lm

### LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>t(1-15)</sub>: 90

MR 0.81

MDER 0.74

### Optical

wallwasher

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

### Electrical

DALI-2

system 27.8 W

inset 23.7 W

36 Vf

650 mA

PC2 220-240V

system 91 lm/W<sup>2</sup>

inset 107 lm/W<sup>3</sup>

### Physical

trim

length 118 mm

width 118 mm

height 96 mm

0.73 kg

### Cutout

length 112 mm


width 112 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 120 mm

### Light distribution



### Product drawing



<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>3</sup> incl. optical losses

### Installation instructions



### Lighting calculator

