

# SASSO 100 square wallwasher

trim

048-2750014A 048-279731G 002-90789



Project / Type


Notes

Count / Date



Recessed square spotlight in die-cast aluminium; 1 lamp; surface matt silver; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling , Recessed  
matt silver  
Mounting set white aluminium  
IP20  
2420 lm

## LED

3000 K  
CRI  $\geq 90$   
L85 / 50000 h  
initial MacAdam  $\leq 3$  SDCM  
 $R_g: 99, R_f: 91, R_{f(1-15)}: 89$   
MR 0.61  
MDER 0.55

## Optical

wallwasher  
 $P_{stLM} \leq 1.0^1$   
 $SVM \leq 0.4^1$

## Electrical

DALI-2  
system 27.8 W  
inset 23.7 W  
36 Vf  
650 mA  
PC2 220-240V  
system 87 lm/W<sup>2</sup>  
inset 102 lm/W<sup>3</sup>

## Physical

trim  
length 118 mm  
width 118 mm  
height 96 mm  
0.73 kg

## Cutout

length 112 mm  
width 112 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 120 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>3</sup> incl. optical losses

## Installation instructions



## Lighting calculator

