

# SASSO 100 round wallwasher/floor trim soft acoustic ceiling

048-2740611W 048-2796397 002-90777



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Recessed
rotation 360°
black , RAL9005 <sup>1</sup>
Signal white
IP20
2000 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>(1-5)</sub> : 89
MR 0.81
MDER 0.74

## Optical

wallwasher floor
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM
system 19.2 W
inset 16.3 W
36 Vf
500 mA
PC2 220-240V
system 104 lm/W <sup>3</sup>
inset 123 lm/W <sup>4</sup>


## Physical

with trim for acoustic ceiling
diameter 114 mm
height 96 mm
0.67 kg


## Cutout

diameter 100 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 100 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses

## Installation instructions



## Lighting calculator

