



048-2730114W 048-279731G 002-90789



Ceiling , Recessed
tilt max 30°
matt silver
Mounting set white aluminium
front IP40 , back IP20
2530 lm
fixture 112 lm/W¹

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 98, R_f: 90, R₍₁₋₁₅₎: 88
MR 0.8
MDER 0.72

| |
|--------------------------|
| wide flood |
| beam angle 65° |
| ≥65° <1500 cd/m² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

| |
|----------------|
| DALI-2 |
| 220-240 V |
| system 26.7 W |
| fixture 22.7 W |
| 36 Vf |
| 650 mA |
| PC2 |
| 1 DALI Addr. |

| | |
|---------------|--|
| trim | |
| length 118 mm | |
| width 118 mm | |
| height 95 mm | |
| 0.53 kg | |

| |
|------------------------------|
| length 112 mm |
| width 112 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm |

² Value of containing product at full load (undimmed)

SASSO 100 square adjustable

trim

048-2730114W 048-279731G 002-90789



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

