


SASSO 100 round adjustable trim soft acoustic ceiling

048-2720119F 048-2796318 002-90767



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Recessed
 tilt max 30°
 rotation 360°
 gold , RAL260-M ¹
 Mounting set Traffic black
 front IP40 , back IP20
 1690 lm

LED

4000 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 98 , R_r: 90 , R_{1-15}: 88
 MR 0.8
 MDER 0.72

Optical

flood
 beam angle 45°
 UGR < 16 , ≥65° <3000 cd/m²
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

DALI-2
 system 17.9 W
 inset 15.2 W
 36 Vf
 450 mA
 PC2 220-240V
 system 94 lm/W³
 inset 111 lm/W⁴
 1 DALI Addr.

Physical


with trim for acoustic ceiling
 diameter 114 mm
 height 95 mm
 0.5 kg

Cutout


diameter 108 mm
 min. ceiling thickness 25 mm
 max. ceiling thickness 40 mm
 recessed depth 100 mm

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 45° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)
⁴ incl. optical losses



SASSO 100 round adjustable trim soft acoustic ceiling

048-2720119F 048-2796318 002-90767



Project / Type

Notes

Count / Date

**Installation
instructions**



**Lighting
calculator**

