

SASSO 100 round adjustable

trim

048-2720114W 048-2796318 002-90767




| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 60° beam; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|-------------------------------|
| Ceiling , Recessed |
| tilt max 30° |
| rotation 360° |
| matt silver |
| Mounting set jet black |
| front IP40 , back IP20 |
| 1830 lm |
| fixture 120 lm/W ¹ |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 98 , R _r : 90 , R _{t(1-15)} : 88 |
| MR 0.8 |
| MDER 0.72 |

Optical

| |
|---------------------------------------|
| wide flood |
| beam angle 60° |
| $\geq 65^\circ < 3000 \text{ cd/m}^2$ |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|----------------|
| DALI-2 |
| 220-240 V |
| system 17.9 W |
| fixture 15.2 W |
| 36 Vf |
| 450 mA |
| PC2 |
| 1 DALI Addr. |

Physical

| |
|-----------------|
| trim |
| diameter 118 mm |
| height 95 mm |
| 0.5 kg |

Cutout

| |
|------------------------------|
| diameter 108 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm |

¹ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.
² Value of containing product at full load (undimmed)



SASSO 100 round adjustable

trim

048-2720114W 048-2796318 002-90767



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

