

SASSO 100 round adjustable

trim

048-2720114S 048-279631G 002-90789




Project / Type	
Notes	
Count / Date	



Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 18° beam; UGR ≤ 16 ; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed	
tilt max 30°	
rotation 360°	
matt silver	
Mounting set white aluminium	
front IP40 , back IP20	
2180 lm	

LED

4000 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 2 SDCM	
R _g : 98 , R _r : 90 , R _{t(1-15)} : 88	
MR 0.8	
MDER 0.72	

Optical

spot	
beam angle 18°	
UGR < 16	
PstLM ≤ 1.0 ¹	
SVM ≤ 0.4 ¹	

Electrical

DALI-2	
system 26.7 W	
inset 22.7 W	
36 Vf	
650 mA	
PC2 220-240V	
system 82 lm/W ²	
inset 96 lm/W ³	
1 DALI Addr.	

Physical

trim	
diameter 118 mm	
height 95 mm	
0.49 kg	

Cutout

diameter 108 mm	
min. ceiling thickness 2 mm	
max. ceiling thickness 25 mm	
recessed depth 100 mm	

¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)
³ incl. optical losses



SASSO 100 round adjustable

trim

048-2720114S 048-279631G 002-90789



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

