

# SASSO 100 round adjustable

trim

048-2720011W 048-279631G 002-90789




|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 60° beam; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

|                              |
|------------------------------|
| Ceiling , Recessed           |
| tilt max 30°                 |
| rotation 360°                |
| black , RAL9005 <sup>1</sup> |
| Mounting set white aluminium |
| front IP40 , back IP20       |
| 2290 lm                      |

## LED

|   |
|---|
| 3000 K  |
| CRI $\geq 90$   |
| L80 / 50000 h   |
| initial MacAdam $\leq 2$ SDCM   |
| R <sub>g</sub> : 99 , R <sub>r</sub> : 90 , R <sub>t(1-15)</sub> : 87 |
| MR 0.6  |
| MDER 0.54   |

## Optical

|                                       |
|---------------------------------------|
| wide flood                            |
| beam angle 60°                        |
| $\geq 65^\circ < 3000 \text{ cd/m}^2$ |
| PstLM $\leq 1.0$ <sup>2</sup>         |
| SVM $\leq 0.4$ <sup>2</sup>           |

## Electrical

|                             |
|-----------------------------|
| DALI-2                      |
| system 26.7 W               |
| inset 22.7 W                |
| 36 Vf                       |
| 650 mA                      |
| PC2 220-240V                |
| system 86 lm/W <sup>3</sup> |
| inset 101 lm/W <sup>4</sup> |
| 1 DALI Addr.                |

## Physical

|                 |
|-----------------|
| trim            |
| diameter 118 mm |
| height 95 mm    |
| 0.49 kg         |

## Cutout

|                              |
|------------------------------|
| diameter 108 mm              |
| min. ceiling thickness 2 mm  |
| max. ceiling thickness 25 mm |
| recessed depth 100 mm        |

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>4</sup> incl. optical losses



# SASSO 100 round adjustable

trim

048-2720011W 048-279631G 002-90789



Project / Type

Notes

Count / Date

Installation instructions



Lighting calculator

