

# SASSO 100 square downlight

trim 2 lamps

048-2710914W 048-2799318 002-90789



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling , Recessed \_\_\_\_\_

matt silver \_\_\_\_\_

Mounting set jet black \_\_\_\_\_

front IP44 , back IP20 \_\_\_\_\_

4680 lm \_\_\_\_\_

### LED

2700 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq$  2 SDCM \_\_\_\_\_

R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 87 \_\_\_\_\_

MR 0.52 \_\_\_\_\_

MDER 0.47 \_\_\_\_\_

### Optical

wide flood \_\_\_\_\_

beam angle 65° \_\_\_\_\_

$\geq 65^\circ$  <1500 cd/m<sup>2</sup> \_\_\_\_\_

PstLM  $\leq$  1.0 <sup>1</sup> \_\_\_\_\_

SVM  $\leq$  0.4 <sup>1</sup> \_\_\_\_\_

Recessed square spotlight in die-cast aluminium; 2 lamps; surface matt silver; installation without tools in mounting set due to patented ball catch system; rectangular installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam  $\leq$  2 SDCM; CRI  $\geq$  90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 65° beam; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Electrical

DALI-2 \_\_\_\_\_

system 52 W \_\_\_\_\_

inset 22.7 W \_\_\_\_\_

36 V \_\_\_\_\_

650 mA \_\_\_\_\_

total insets 45 W \_\_\_\_\_

PC2 220-240V \_\_\_\_\_

system 90 lm/W<sup>2</sup> \_\_\_\_\_

inset 103 lm/W<sup>3</sup> \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

### Physical

trim \_\_\_\_\_

length 218 mm \_\_\_\_\_

width 118 mm \_\_\_\_\_

height 75 mm \_\_\_\_\_

0.59 kg \_\_\_\_\_

### Cutout

length 210 mm \_\_\_\_\_


width 112 mm \_\_\_\_\_

min. ceiling thickness 2 mm \_\_\_\_\_


max. ceiling thickness 25 mm \_\_\_\_\_

recessed depth 100 mm \_\_\_\_\_

### Light distribution



### Product drawing



# SASSO 100 square downlight

trim 2 lamps

048-2710914W 048-2799318 002-90789



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

