

SASSO 100 square downlight

trim

048-2710117M 048-279731G 002-90767



Project / Type


Notes

Count / Date




Recessed square spotlight in die-cast aluminium; 1 lamp; surface white; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim white aluminium; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 34° beam; UGR ≤ 19 ; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed
white , RAL9016 ¹
Mounting set white aluminium
front IP44 , back IP20
1640 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
 $R_g: 98$, $R_r: 90$, $R_{t(1-15)}: 88$
MR 0.8
MDER 0.72

Optical

medium
beam angle 34°
UGR < 19
 $P_{stLM} \leq 1.0$ ²
 $SVM \leq 0.4$ ²

Electrical

DALI-2
system 17.9 W
inset 15.2 W
36 V
450 mA
PC2 220-240V
system 92 lm/W³
inset 108 lm/W⁴
1 DALI Addr.

Physical

trim
length 118 mm
width 118 mm
height 75 mm
0.54 kg

Cutout

length 112 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 80 mm

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. optical losses and the efficiency of the operating device (converter)
⁴ incl. optical losses



SASSO 100 square downlight

trim

048-2710117M 048-279731G 002-90767



Project / Type

Notes

Count / Date

Installation
instructions



Lighting
calculator

