

SASSO 100 square downlight

trim 2 lamps

048-2710014W 048-2799317 002-90767



Project / Type	
Notes	
Count / Date	



--	--	--

General

Ceiling , Recessed
matt silver
Mounting set traffic white
front IP44 , back IP20
3540 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99 , R _r : 90 , R _{t(1-15)} : 87
MR 0.6
MDER 0.54

Optical


wide flood
beam angle 65°
≥65° <1500 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Recessed square spotlight in die-cast aluminium; 2 lamps; surface matt silver; installation without tools in mounting set due to patented ball catch system; rectangular installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 65° beam; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Electrical

DALI-2
system 35 W
inset 15.2 W
36 V _f
450 mA
total insets 30 W
PC2 220-240V
system 101 lm/W ²
inset 116 lm/W ³
1 DALI Addr.

Light distribution



Product drawing



Physical

trim
length 218 mm
width 118 mm
height 75 mm
0.6 kg

Cutout

length 210 mm
width 112 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

¹ Value of containing product at full load (undimmed)
² incl. optical losses and the efficiency of the operating device (converter)
³ incl. optical losses



SASSO 100 square downlight

trim 2 lamps

048-2710014W 048-2799317 002-90767



Project / Type

Notes

Count / Date

Installation
instructions



Lighting
calculator

