

# SASSO 100 square downlight

trimless

048-2710011S 048-2797117 002-90767



Project / Type	
Notes	
Count / Date	



--	--	--	--

### General

Ceiling , Recessed
black , RAL9005 <sup>1</sup>
Mounting set traffic white
front IP44 , back IP20
1450 lm

### LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 87
MR 0.6
MDER 0.54

### Optical

spot
beam angle 19°
UGR < 13 , ≥65° <3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2
system 17.9 W
inset 15.2 W
36 Vf
450 mA
PC2 220-240V
system 81 lm/W <sup>3</sup>
inset 95 lm/W <sup>4</sup>
1 DALI Addr.

### Physical


trimless
length 105 mm
width 105 mm
height 75 mm
0.52 kg

### Cutout

length 106 mm
width 106 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 25 mm
recessed depth 80 mm

Recessed square spotlight in die-cast aluminium; 1 lamp; surface black; installation without tools in mounting set due to patented ball catch system; square installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 19° beam; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m<sup>2</sup>; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



# SASSO 100 square downlight

trimless

048-2710011S 048-2797117 002-90767



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

