

048-2700219M 048-2796398 002-90789



Project / Type

Notes

Count / Date



Ceiling, Recessed
gold, RAL 260-M ¹
Mounting set traffic black for acoustic ceilings
front IP44, back IP20
2070 lm
fixture 91 lm/W²

3500 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 99, R _f : 90, R _{1-15} : 89
MR 0.7
MDER 0.64

medium
beam angle 33°
UGR ≤ 16, ≥65° <3000 cd/m²
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³

DALI-2
220-240 V
system 26.7 W
fixture 22.7 W
36 Vf
650 mA
PC2
1 DALI Addr.

with trim for acoustic ceiling
diameter 114 mm
height 75 mm
0.49 kg

diameter 100 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 80 mm

Technical drawing of a part with dimensions 80, 100, and 75. The drawing includes a side view, a top view, and a cross-section view.

[048-2700219M 048-2796398 002-90789'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

20.04.2025

1/1

