

# SASSO 40 round downlight

trim 2 lamps

048-2800517M 048-2898318 002-90752




Project / Type
Notes
Count / Date



Round recessed spotlight in die-cast aluminium; 2 lamps; surface white; , installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 25° beam; UGR  $\leq 13$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65°  $\leq 1500$  cd/m<sup>2</sup>; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling , Recessed
rotation 360°
white , RAL 9016 <sup>1</sup>
jet black
front IP44 , back IP20
810 lm
fixture 79 lm/W <sup>2</sup>

## LED

4000 K
CRI $\geq 90$
L85 / 50000 h
initial MacAdam $\leq 3$ SDCM
R <sub>g</sub> : 94 , R <sub>r</sub> : 87 , R <sub>(1-15)</sub> : 90
MR 0.86
MDER 0.78

## Optical

medium
beam angle 25°
UGR $< 13$ , $\geq 65^\circ < 1500$ cd/m <sup>2</sup>
PstLM $\leq 1.0$ <sup>3</sup>
SVM $\leq 0.4$ <sup>3</sup>

## Electrical

non DIM
220-240 V
system 12.0 W
fixture 5.1 W
12 Vf
450 mA
fixture 10.2 W
PC2

## Physical

trim
length 122 mm
width 60 mm
height 50 mm
0.61 kg

## Cutout

diameter 56 mm
length 114 mm
width 114 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 120 mm

<sup>1</sup> RAL code  
<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.  
<sup>3</sup> Value of containing product at full load (undimmed)



# SASSO 40 round downlight

trim 2 lamps

048-2800517M 048-2898318 002-90752



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

