

SASSO 100 round adjustable trim soft acoustic ceiling

048-2720114M 048-2796397 002-90780



Project / Type

Notes

Count / Date



General
Ceiling , Recessed
tilt max 30°
rotation 360°
matt silver
Mounting set signal white for acoustic ceilings
front IP40 , back IP20
2180 lm


LED
4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 98 , R _r : 90 , R _{t1-15} : 88
MR 0.8
MDER 0.72

Optical
medium
beam angle 32°
UGR < 16 , ≥65° <3000 cd/m²


Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim signal white for acoustic ceilings; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 32° beam; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; degree of protection from below IP40 (from above IP20); PC2; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical
non DIM
220-240 V
system 26.7 W
inset 22.7 W
36 Vf
650 mA
PC2
system 82 lm/W ¹
inset 96 lm/W ¹

Light distribution



Product drawing



Physical
with trim for acoustic ceiling
diameter 114 mm
height 95 mm
0.45 kg

Cutout
diameter 100 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 100 mm

¹ incl. optical losses and the efficiency of the operating device (converter)

Installation instructions

Lighting calculator

