

# SASSO 100 round adjustable trim soft acoustic ceiling

048-2720017W 048-2796397 002-90766



Project / Type


Notes

Count / Date




Round recessed spotlight in die-cast aluminium; 1 lamp; surface white; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim signal white for acoustic ceilings; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 59° beam; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling , Recessed  
tilt max 30°  
rotation 360°  
white , RAL 9016 <sup>1</sup>  
Mounting set signal white for acoustic ceilings  
front IP40 , back IP20  
1740 lm  
fixture 114 lm/W<sup>2</sup>

## LED

3000 K  
CRI  $\geq 90$   
L80 / 50000 h  
initial MacAdam  $\leq 2$  SDCM  
R<sub>g</sub>: 99 , R<sub>r</sub>: 90 , R<sub>t-15</sub>: 87  
MR 0.6  
MDER 0.54

## Optical

wide flood  
beam angle 59°  
PstLM  $\leq 1.0$  <sup>3</sup>  
SVM  $\leq 0.4$  <sup>3</sup>

## Electrical

non DIM  
220-240 V  
system 17.9 W  
fixture 15.2 W  
36 Vf  
450 mA  
PC2

## Physical

with trim for acoustic ceiling  
diameter 114 mm  
height 95 mm  
0.47 kg

## Cutout

diameter 100 mm  
min. ceiling thickness 25 mm  
max. ceiling thickness 40 mm  
recessed depth 100 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

