

MINO CIRCLE ACOUSTIC

1500

ceiling


034-271211B



Project / Type

Notes

Count / Date



General

Ceiling , Surface

anthracite

Physical

diameter 1434 mm

height 24 mm

8.4 kg

Acoustics

Alpha w (α_w) up to 0.7

SAC (sound absorption class) up to C

NRC up to 1.15

SAA up to 1.16


Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50% post-consumer recycled PET; round design; high quality visual and tactile surface, anthracite; colour may deviate; absorption of direct sound; this creates high acoustic performance; for ceiling surface mounting;

Product drawing



MINO CIRCLE ACOUSTIC 1500

ceiling
034-271211B



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

| 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ |
|--------|--------|--------|---------|---------|---------|
| 0.3 | 0.6 | 1.43 | 2.3 | 2.17 | 2.1 |

Sound absorption coefficient (α_p)

