

MINO CIRCLE ACOUSTIC 1500


inlay
034-270211B



Project / Type

Notes

Count / Date



General

Luminaire / Track , Mounted

anthracite

Physical

diameter 1434 mm

height 24 mm

7.1 kg

Acoustics

Alpha w (α_w) up to 0.65

SAC (sound absorption class) up to C

NRC up to 0.7

SAA up to 0.74


Acoustic data calculations based on MINO CIRCLE ACOUSTIC 1000, cavity 100cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of 50% recycled PET; round design; high quality visual and tactile surface, anthracite; colour may deviate; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for insertion into the MINO 60 CIRCLE 1500 ceiling or MINO 60 CIRCLE 1500 suspended;

Product drawing



MINO CIRCLE ACOUSTIC 1500

inlay
034-270211B



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.97	1.2	1.83	2.67	3.07	3.3

Sound absorption coefficient (a_p)

