

# INDIRECT low power

MOVE IT PRO

086-6820230B



Project / Type

Notes

Count / Date



## General

Ceiling , Track  
indirect batwing low power  
white  
IP20  
1930 lm  
1320 lm/m

## LED

3500 K  
CRI  $\geq$  90  
L90 / 50000 h  
initial MacAdam  $\leq$  3 SDCM  
 $R_g$ : 96 ,  $R_f$ : 90 ,  $R_{f(1-15)}$ : 91  
MR 0.74  
MDER 0.67

## Optical

batwing  
UGR  $\leq$  10 ,  $\geq 65^\circ$   $< 1500$  cd/m<sup>2</sup>  
PstLM  $\leq$  1.0<sup>1</sup>  
SVM  $\leq$  0.4<sup>1</sup>

## Electrical

DALI-2  
220-240 V  
system 17.7 W  
system 109 lm/W<sup>2</sup>  
PC2  
1 DALI Addr.  
12 W/m

## Physical


length 1472 mm  
width 24 mm  
height 6 mm

<sup>1</sup> Value of containing product at full load (undimmed)

<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

