

# INDIRECT EXTENSION low power MOVE IT PRO

086-6800930B



Project / Type


Notes

Count / Date



Linear light inset made of plastic; light inset can be installed flexibly and without tools; flush with profile system; power supplied via INDIRECT MOVE IT PRO inset; with indirect light component for additional accentuation of the ceiling; high quality lens system for maximum, homogeneous ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; light source replaceable by an authorized professional;

## Light distribution



## General

Ceiling , Track Suspended

low power

white

IP20

374 lm

## LED

2700 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.48

MDER 0.44

## Optical

batwing

UGR  $\leq 10$  ,  $\geq 65^\circ$  <1500 cd/m<sup>2</sup>

## Electrical

system 2.8 W

fixture 2.4 W

system 134 lm/W<sup>1</sup>

50 mA

PC3

## Physical

length 245 mm

width 24 mm

height 6 mm

<sup>1</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions



## Lighting calculator

